

TRIGGER SWITCH MODULE

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

10 The present invention relates to a trigger switch module, and more particularly to a trigger switch module that can be used with various kinds of household appliances, lighting fixtures, instruments, etc. to generate a signal needed by a microcontroller via a human-machine interface, so that programs and circuit designs for peripheral hardware can be done more conveniently, and the electronic trigger switch can
15 operate through a non-direct contact with the switch. With the trigger switch module, conventional switches and related products are upgraded to the rank of microcomputer-type touch-controlled products that have increased added value.

20

2. Description of the Prior Art

25 A conventional mechanical-type switch is subject to fatigue phenomenon and even fatigue failure due to frequent mechanical movements during its service over a long time. On the other hand, technical skills related to applied electronic products are constantly developed and innovated in recent years, resulting in the presentation of a variety of trigger switches that
30 have been widely and frequently used to gradually

replace the mechanical-type switches. The up-to-date electronic trigger switches have become very popular and eliminate drawbacks existing in the convention mechanical-type switches. One of the most welcomed
5 electronic trigger switches is a touch switch that is widely employed on indoor lighting fixture and general household appliances. Most currently available touch switches are triggered through contacting a conducting body by a user, and static charge is grounded via the
10 user's body. That is, most touch switches operate according to a change in static field energy or a direct trigger of an internal control circuit thereof, or utilize a user's body resistance to perform electrical connection or impedance detection between two
15 conducting bodies. The above-mentioned triggering of touch switch is achieved through direct contact of the user's finger with a metal member of the touch switch. In the event the touch switch does not include a control circuit to provide good safety measures, a user might
20 very possibly be injured due to many external factors, such as leakage, shock, etc., at the moment of contacting the touch switch. That is, the currently available touch switches do not provide necessary safety means and therefore adversely affect the user's
25 safety in using products having touch switches.

It is therefore desirable to improve the safety design for trigger switches to eliminate drawbacks existing in the currently available touch switches.

SUMMARY OF THE INVENTION

4083364 "032702"
A primary object of the present invention is to provide
5 a trigger switch module in which a signal needed by
a microcontroller is generated via a human-machine
interface, and stable signal level output pins are
included, so that a microprocessor or a logic gate can
make judgment easily. The electronic trigger switch
10 signal is triggered through a non-direct contact of
the switch to send out signal. The trigger switch
module of the present invention has low power
consumption, wide service voltage, and fewer external
components to provide designers with high flexibility
15 in using the switch. The trigger switch module of the
present invention combines the functions of
conventional slide switches and button switches but
eliminates drawbacks existing in these conventional
switches.

20
Another object of the present invention is to provide
a modularized trigger switch, so that the entire
trigger switch is provided in an enclosed space, in
which humidity or other media that might affect or
25 change capacity of the switch are not influenced by
air convection outside the enclosed space to cause
unstable capacity. In brief, circuit elements and
other components and parts of a non-modularized
trigger switch are exposed to external environment.
30 Flows of ambient air would result in increased or

decreased humidity that is a factor adversely affecting the stable capacity of the trigger switch. By way of modularization, the trigger switch has a highly stable capacity, which is equal to body capacity,
5 to perform the on/off function.

A further object of the present invention is to provide a trigger switch module that has an operating mode of utilizing signals needed by a microcontroller and can
10 therefore include a touch panel that is not limited to plastics, metals, but can include a wide range of other materials, such as glass, ceramic, wood, stone, etc., so that the touch panel may have a variety of designs for use with various household appliances and
15 code-controlled devices and switches.

A still further object of the present invention is to provide a trigger switch module that can be triggered through non-direct contact of the switch, so that a
20 product with such trigger switch module is upgraded to the rank of microcomputer-type touch-controlled products. All the components of the trigger switch module are enclosed in a non-metal casing and fully protected against water and dust, so that the trigger
25 switch module has increased added value and a widened range of application.

BRIEF DESCRIPTION OF THE DRAWINGS

30 The structure and the technical means adopted by the

present invention to achieve the above and other objects can be best understood by referring to the following detailed description of the preferred embodiments and the accompanying drawings, wherein

5

Fig. 1 is a circuit diagram of the present invention;

Fig. 2 is a schematic plan view of a preferred embodiment of the present invention;

10

Fig. 3 is an exploded perspective view of a switch element of the present invention; and

Fig. 4 is a schematic plan view of another embodiment of the present invention.

15

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Please refer to Fig. 1 that is a circuit diagram of a trigger switch module according to the present invention. As shown, the present invention includes a circuit board 10 on which there is provided a control circuit 11, a grounding end 12 via which the trigger switch module is grounded, a power input 13 via which power is supplied to the trigger switch module, a light-emitting diode (LED) 14 serving as a touch indicating lamp, a signal output 15 via which a signal is sent out, a contact end 16 at where a user touches to trigger the switch, and sensors 17, 18 for sensing a touch of user at the touch end 16 and causing the

20

25

30

signal end 15 to output a signal. The sensors 17, 18 may have sensibility adjustable according to a user's requirement.

5 Please refer to Fig. 2 that is a schematic plan view of a trigger switch module according to a preferred embodiment of the present invention. As shown, the trigger switch module mainly includes a switch element 20, an end of which is inserted onto the above-mentioned circuit board 10, and another end of which is covered with a touch panel 30. For the switch to be durable and safe for use, the touch panel 30 is made of an insulating material and has a thickness H adjustably designed in accordance with users' individual requirements. The materials for the touch panel 30 are not limited to conventional plastics or metals. Any other material that can be easily fabricated and machined, such as glass, ceramic, wood, stone, and the like, can also be employed to make the touch panel 30, so long as the material is able to prevent occurrence of direct electric shock and reduce the influence of electric current on human body. In this manner, a variety of touch panels may be provided for the trigger switch module of the present invention.

25

Fig. 3 is an exploded perspective view of the switch element 20. As shown, the switch element 20 includes a top casing 22, a sensing board 23 located below the top casing 22, a connecting element 24 located below the sensing board 23, and a plurality of pins 25 having

a first end inserted into the connecting element 24 and a second end inserted onto a circuit board 26. A distance between the sensing board 23 and the circuit board 26 is set according to body capacity. When the switch element 20 is fully assembled into one unit, a user needs only to lightly push the switch element 20 or the touch panel 30 for the sensing board 23 to sense the body capacity and trigger the switch.

- 10 While a proper distance between the sensing board 23 and the circuit board 26 via the connecting element 24 enabling setting of body capacity for the trigger switch module, air convection would cause unstable humidity and deviation of capacity to fail the switch.
- 15 To protect the trigger switch from failure caused by such factors, the sensing board 23, the connecting element 24, the pins 25, and the circuit board 26 all are assembled and enclosed in the top casing 22 to form a module, so that a stable capacity could be obtained
- 20 in the enclosed top casing 22.

The switch element 20 may have shape, dimensions, distance of sensing, and panel switch module all designed in accordance with users' individual requirements.

To trigger the switch, a user needs only to contact the touch panel 30. At this point, a body capacity effect would cause the sensors 17, 18 on the circuit board 10 to sense changes in the position of the touch

